

The automatic stainless steel AISI 304 hose reels with spring are suitable to hold flexible hoses for diesel delivery. They allow to unroll only the necessary hose length, improving their functionality.

FX-460



FX-550



FX-555



FX-560



Equipped with:

Antistatic black rubber hose 10 bar

Stainless steel connection

Stainless steel swivel joint 90° AISI 316

Viton seals

Ref.	Flow rate	Hose lenght	Ø hose	Inlet-Outlet
	l/min	m	G	
070-2308-500	80	without hose	-	F3/4"G-M1"G
070-2308-508	80	8	3/4"	F3/4"G-M1"G

Ref.	Flow rate	Hose lenght	Ø hose	Inlet-Outlet
	l/min	m	G	

070-2408-600	95	without hose	-	F1"G - M1"G
070-2408-510	85	10	3/4"	F1"G - M1"G
070-2408-515	85	15	3/4"	F1"G - M1"G
070-2408-610	93	10	1"	F1"G - M1"G

Ref.	Flow rate	Hose lenght	Ø hose	Inlet-Outlet
	l/min	m	G	

070-2508-600	95	without hose	-	F1"G - M1"G
070-2508-520	83	20	3/4"	F1"G - M1"G
070-2508-615	90	15	1"	F1"G - M1"G

Ref.	Flow rate	Hose lenght	Ø hose	Inlet-Outlet
	l/min	m	G	

070-2608-600	95	without hose	-	F1"G - M1"G
070-2608-530	80	30	3/4"	F1"G - M1"G
070-2608-540	75	40	3/4"	F1"G - M1"G
070-2608-620	87	20	1"	F1"G - M1"G
070-2608-630	85	30	1"	F1"G - M1"G