

Electric pumps 12V e 230V suitable for per inflammable fuel transfer such as gasoline, kerosene and diesel, with internal protection integrated in the winding. The electric pumps for gasoline transfer fulfill the standards of ATEX / IECEx directives regarding the use of materials in potentially explosive atmospheres (see ATEX Regulations at page 179).



Art. 091-5800-050
Electric pump ATEX for gasoline transfer
230V-50Hz Flow rate 50l/min



Power cable 2 m lenght, Schuko plug
 Cast iron body
 High efficiency engine with reduced absorption
 Suppressor (electromagnetic compatibility EMC)
 Built-in by-pass valve
 Thermic protection

Art. 091-5801-050
Electric pump ATEX for gasoline transfer
12V Flow rate 50l/min



Power cable 2 m lenght, with pincers and protection fuse
 Cast iron body
 High efficiency engine with reduced absorption
 Suppressor (electromagnetic compatibility EMC)
 Built-in by-pass valve
 Thermic protection

Ref.	Flow rate	Voltage	Power	Electricity	Power cable lenght	Inlet-Out-let	Duty cycle	Weight	Packaging
	l/min	AC V./Hz DC Volt	W	A	m	BSPG	ON/OFF min	kg	mm

091-5800-050	50	230/50	250	1,2	2	F 1"-F 1"	30/30	8,80	390X195X260
---------------------	-----------	--------	-----	-----	---	-----------	-------	------	-------------

091-5801-050	50	12	250	21	2	F 1"-F 1"	30/60	8,80	390X195X260
---------------------	-----------	----	-----	----	---	-----------	-------	------	-------------