

The automatic hose reels with springs in varnished steel are suitable to hold flexible hoses for the AdBlue® delivery. They allow to untwist quickly only the necessary length, improving the working and functionality.

Composed by:

Antistatic black rubber hose EPDM 20 bar  
Stainless steel connections AISI 316  
Stainless steel swiveling joint 90° AISI 316  
Viton seals

**F-400**



| Ref. | Hose lenght | Ø hose | Inlet-outlet |
|------|-------------|--------|--------------|
|      | m           | G      |              |

|                     |              |      |                   |
|---------------------|--------------|------|-------------------|
| <b>070-1209-400</b> | without hose | -    | M 1/2"G - M 1/2"G |
| <b>070-1209-410</b> | 10           | 1/2" | M 1/2"G - M 1/2"G |

**F-460**



| Ref. | Hose lenght | Ø hose | Inlet-outlet |
|------|-------------|--------|--------------|
|      | m           | G      |              |

|                     |              |      |                   |
|---------------------|--------------|------|-------------------|
| <b>070-1309-400</b> | without hose | -    | M 1/2"G - M 1/2"G |
| <b>070-1309-415</b> | 15           | 1/2" | M 1/2"G - M 1/2"G |

**F-550**



| Ref. | Hose lenght | Ø hose | Inlet-outlet |
|------|-------------|--------|--------------|
|      | m           | G      |              |

|                     |              |      |                   |
|---------------------|--------------|------|-------------------|
| <b>070-1409-500</b> | without hose | -    | F 3/4"G - M 3/4"G |
| <b>070-1409-510</b> | 10           | 3/4" | F 3/4"G - M 3/4"G |
| <b>070-1409-515</b> | 15           | 3/4" | F 3/4"G - M 3/4"G |