

Diesel transfer system for private usage, it allows the quick and safe filling of vehicles, and permits to measure and record the dispensed quantities. It is equipped with nozzle holder, microswitch to turn the pump on/off, automatic nozzle with swiveling joint, and extractable hose support. The equipment can be fixed to the wall, to a tank or to its own support column.

“Cami Dispenser” series composed by:



Art. 091-5081-060 12V Pump - power cable (sec. 4 mmq, 4 m lenght)
with pincers and fuse- 60 l/min



Art. 091-5083-060 24V Pump - power cable (sec. 4 mmq, 4 m lenght)
with pincers and use carrier - 60 l/min



Art. 091-5095-060 Electric pump 230V 50Hz 60 l/min

Art. 091-5098-070 Electric pump 230V 50Hz 70 l/min

Art. 091-5100-100 Electric pump 230V 50Hz 100 l/min



Art. 091-5099-070 Electric pump 115V 60Hz 70 l/min

Art. 091-5101-100 Electric pump 115V 60Hz 100 l/min



Art. 908-0516-040 Connection hose ø 20 mm M-M 1” 4 m lenght

Art. 908-0616-040 Connection hose ø 25 mm M-M 1” 4 m lenght



Art. 093-5210-000 Automatic nozzle PA60 Flow rate 70 l/min

Art. 093-5220-000 Automatic nozzle PA120 Flow rate 120 l/min



Art. 092-5103-000 Mechanical flow meter 3 digits F1” 120 l/min - 3C

Art. 092-5104-000 Mechanical flow meter 4 digits F1” 120 l/min - 4C



OPTIONAL:

Art. 090-5072-000 Support column Cami-Dispenser

Art. 094-5240-000 Water separating delivery filter for diesel 70 l/min

Art. 094-5245-000 Water separating delivery filter for diesel 150 l/min