

Combined tank for Diesel and AdBlue® transport for private use in total exemption for ADR (see ADR Regulation at page 180). Made of polyethylene with reinforced lockable lid. Diesel compartment with aluminium filling plug and integrated safety valve, AdBlue® compartment polyethylene plug. Complete with tank level indicator and suction filter only for diesel compartment. The tank is provided with chamfers to be lifted when it is full and grips to be lifted when empty. It is equipped with slots for positioning the fastening belts at the support base. Diesel and AdBlue® compartments supplied with 4 m long cable with pincers for the connection to power battery supply.

“Diesel-AdBlue® Tank” series composed by:



Art. 090-6450-000 Only 400 l Tank + 50 l without pump



Art. 091-5081-045 12V Pump - power cable (sec. 4 mmq, 4 m length) with pincers and fuse - 45 l/min



Art. 098-6000-012 AdBlue® submerged pump 12V-15 l/min power cable (sec. 2,5 mmq. 4 m length) with pincers and fuse



Art. 092-5124-000 Digital turbine flow meter MEC 24 min/max flow rate 7/120 l/min



Art. 908-0516-040 Connection hose ø 20 mm M-M 1" 4 m length for diesel



Art. 909-0500-040 Delivery hose EPDM ø 19x29 mm M-M 4 m length for AdBlue®



Art. 099-5199-000 Manual plastic nozzle “AD90” Flow rate 90 l/min



Art. 093-5210-000 Automatic nozzle PA60 Flow rate 70 l/min



Art. 092-6000-220 Probe for tank 330 l - 440 l