

ELECTRIC PUMPS FOR DIESEL FUEL TRANSFER

Electric pumps 115 - 230V - 400V, volumetric self-priming vane. They are equipped with asynchronous induction self-ventilated with motor protection rating IP55, insulation class type F, internal protection. Built-in by-pass valve and stainless steel filter.



Electric pump 70 l for diesel fuel transfer equipped with:

Power cable 2 m length, Schuko plug

Self-priming rotary electric pump

Cast iron body

By-pass valve

AC Engine

Stainless steel filter 100 micron

Motor protection rating IP55

Ref.	Flow rate	Voltage	Power	Electricity	Cable length	Inlet-outlet	Duty cycle	Weight	Packaging
	l/min	AC V./Hz	W	A	m	BSPG	min	kg	mm

091-5098-070	70	230/50	552	2,9	2	F 1"-F 1"	Contin.	8,60	300X215X230
---------------------	-----------	--------	-----	-----	---	-----------	---------	------	-------------

091-5099-070	70	115/60	575	6	2	F 1"-F 1"	Contin.	8,60	300X215X230
---------------------	-----------	--------	-----	---	---	-----------	---------	------	-------------

091-5097-070	70	400/50	304	1,1	2	F 1"-F 1"	Contin.	9,00	300X215X230
---------------------	-----------	--------	-----	-----	---	-----------	---------	------	-------------

Dimensions:

