



**024-1249-A00**

**Art. 024-1249-A00**

Oil mechanical nozzle Composed by:  
Oil mechanic flow meter (Art.024-1249-000)  
Handle with F 1/2" swivel joint  
Flexible end 105°  
Manual drop valve Ø 12 mm



**024-1249-B00**

**Art. 024-1249-AG0**

Oil mechanical nozzle in gallons

**Art. 024-1249-B00**

Oil mechanical nozzle Composed by:  
Oil mechanic flow meter (Art.024-1249-000)  
Handle with F 1/2" swivel joint  
Rigid end 45°  
Manual drop valve Ø 12 mm



**024-1249-C00**

**Art. 024-1249-BG0**

Oil mechanical nozzle in gallons

**Art. 024-1249-C00**

Oil mechanical nozzle Composed by:  
Oil mechanic flow meter (Art.024-1249-000)  
Handle with F 1/2" swivel joint  
Flexible end 105°  
Automatic drop valve Ø 14 mm



**024-1249-D00**

**Art. 024-1249-CG0**

Oil mechanical nozzle in gallons

**Art. 024-1249-D00**

Oil mechanical nozzle Composed by:  
Oil mechanic flow meter (Art.024-1249-000)  
Handle with F 1/2" swivel joint  
Rigid end 45°  
Automatic drop valve Ø 14 mm



**024-1249-000**

**Art. 024-1249-DG0**

Oil mechanical nozzle in gallons

**Art. 024-1249-000**

Oil mechanical flow meter  
It is equipped 3 figures + 1 decimal.  
Display 6 figures rekittable

**Art. 024-1249-G00**

Oil mechanical nozzle in gallons

| Technical Data          | 024-1249-000  | 024-1249-G00     |
|-------------------------|---------------|------------------|
| Inlet/outlet connection | F 1/2" BSP    | F 1/2" BSP       |
| Pressure min/max        | 0,35 - 70 bar | 5 - 1000 Psi     |
| Flow min/max            | 1 - 30 l/min  | 0,20 - 8 gal/min |
| Accuracy                | +/- 0,1%      | +/- 0,1%         |

**FEATURES**

- Calibration is not necessary
- Easy rekit
- Partial and total totalizer
- Non-rekittable total totalizer
- Batteries are not necessary
- Mechanical rekit button
- Not approved for public usage