



025-1272-000



025-1274-000

**Art. 025-1272-000**

Connection 1" G - M40X1,25

It connects the pump to the modular extensions

**Art. 025-1274-000**

Connection M 40X1,25

Allow the connection between the modular extensions

**Art. 025-1275-025**

Ø 42 mm 250 mm length extension

Thread F-F M 40X1,25

**Art. 025-1275-050**

Ø 42 mm 500 mm length extension

Thread F-F M 40X1,25

**Art. 025-1275-092**

Ø 42 mm 912 mm length extension

Thread F-F M 40X1,25

**Art. 025-1275-122**

Ø 42 mm 1212 mm length extension

Thread F-F M 40X1,25

**Art. 025-1276-000**

Oil shank end with filter Ø 42 mm

Thread M 40X1,25

025-1276-000



025-1275-025



025-1275-050



025-1275-092



025-1275-122



**Stainless steel 90° connection**



R18-1250-006



R18-1251-006

Article	Inlet-Outlet	Max pressure	Metal	Weight
R18-1250-006	M1" - F1"	100 bar	SS AISI 316	0,137 kg
R18-1251-006	F1" - F1"	100 bar	SS AISI 316	0,158 kg

**Stainless steel connection fixed rubber hose**

Article	Inlet	Ø hose	Metal	Weight
R18-0821-256	M1"	25 mm	SS AISI 316	0,137 kg

**Y-shaped nickel-plated brass in-line filter**

Article	Inlet	Ø hose	Metal	Weight
R18-0855-255	M3/4"	25 mm	Brass	0,084 kg
R18-0855-206	M1"	20 mm	Brass	0,095 kg
R18-0855-256	M1"	25 mm	Brass	0,126 kg

**Stainless steel connection fixed rubber hose**

Article	Inlet	Ø hose	Metal	Weight
R18-0803-206	M1"	20 mm	Galvanized steel	0,095 kg
R18-0803-256	M1"	25 mm	Galvanized steel	0,105 kg

**Y-shaped nickel-plated brass in-line filter**

Article	Inlet-Outlet	Max pressure	Filter	Weight
R34-0002-004	F1/2" - F1/2"	100 bar	400 µm	0,160 kg
R34-0002-005	F3/4" - F3/4"	100 bar	400 µm	0,220 kg
R34-0002-006	F1" - F1"	100 bar	400 µm	0,330 kg



R18-0855-256



R18-0821-256



R18-0803-206



R18-0803-256



R34-0002-006