

Art. 027-1306-000

24 I pneumatic oil dispenser

Composed by:

Tank capacity 24 I (with level indicator)


Delivery hose Ø 12 mm spring PU hose 3 m length (027-1303-030)

Oil digital nozzle (Art.024-1233-A00)

With flexible end manual drop valve Ø 12 mm

Funnel to fill the tank

| | | | |
|---------------------|--------|-------|---|
| | | | |
| 027-1306-000 | 12,900 | 0,074 | 1 |



027-1306-000

Art. 027-1308-000

24 I pneumatic oil dispenser stainless steel

Composed by:

Tank capacity 24 I (with level indicator)


Delivery hose Ø 12 mm spring PU hose 3 m length (027-1303-030)

Oil digital nozzle (Art.024-1233-A00)

With flexible end manual drop valve Ø 12 mm

Funnel to fill the tank

| | | | |
|---------------------|--------|-------|---|
| | | | |
| 027-1308-000 | 11,600 | 0,074 | 1 |



027-1308-000

Art. 027-1312-000

50 I pneumatic oil dispenser

Composed by:

Tank capacity 50 I (with level indicator)


Delivery hose Ø 12 mm spring PU hose 3 m length (027-1303-030)

Oil digital nozzle (Art.024-1233-A00)

With flexible end manual drop valve Ø 12 mm

Funnel to fill the tank

| | | | |
|---------------------|--------|-------|---|
| | | | |
| 027-1312-000 | 24,100 | 0,152 | 1 |



027-1312-000

They are advised for the filling and maintenance of oil. The tank has to be filled for 4/5 of its capacity and when air is put inside at 6-8 bar it works automatically without any continuous link to compressed air.