


Model DAMP 35

Max flow rate: 35 l/min
 Fluid connections: 3/4" BSP


ARTICLE	CASING	FLUID CONNECTION	AIR CONNECTION	MAX PRESSURE	MAX FLOW RATE
A28-0035-001	POLYPROPYLENE	3/4" BSP	6 mm	8 bar	35 l/min
A28-0035-002	PVDF	3/4" BSP	6 mm	8 bar	35 l/min
A28-0035-003	POMc	3/4" BSP	6 mm	8 bar	35 l/min
A28-0035-004	SS AISI 316	3/4" BSP	6 mm	8 bar	35 l/min



Model DAMP 110

Max flow rate: 110 l/min
 Fluid connections: 1" BSP


ARTICLE	CASING	FLUID CONNECTION	AIR CONNECTION	MAX PRESSURE	MAX FLOW RATE
A28-0110-001	POLYPROPYLENE	1" BSP	8 mm	8 bar	110 l/min
A28-0110-002	PVDF	1" BSP	8 mm	8 bar	110 l/min
A28-0110-003	POMc	1" BSP	8 mm	8 bar	110 l/min
A28-0110-004	SS AISI 316	1" BSP	8 mm	8 bar	110 l/min



Model DAMP 250

Max flow rate: 250 l/min
 Fluid connections: 1" 1/2 BSP

ARTICLE	CASING	FLUID CONNECTION	AIR CONNECTION	MAX PRESSURE	MAX FLOW RATE
A28-0250-001	POLYPROPYLENE	1.1/2" BSP	10 mm	8 bar	250 l/min
A28-0250-002	PVDF	1.1/2" BSP	10 mm	8 bar	250 l/min
A28-0250-003	POMc	1.1/2" BSP	10 mm	8 bar	250 l/min
A28-0250-004	SS AISI 316	1.1/2" BSP	10 mm	8 bar	250 l/min



Model DAMP 1000

Max flow rate: 1000 l/min
 Fluid connections: 2" BSP

ARTICLE	CASING	FLUID CONNECTION	AIR CONNECTION	MAX PRESSURE	MAX FLOW RATE
A28-1000-001	POLYPROPYLENE	2" BSP	12 mm	8 bar	1000 l/min
A28-1000-002	PVDF	2" BSP	12 mm	8 bar	1000 l/min
A28-1000-003	ALLUMINIO	2" BSP	12 mm	8 bar	1000 l/min
A28-1000-004	SS AISI 316	2" BSP	12 mm	8 bar	1000 l/min