# **EXHAUSTED OIL DRAIN UNITS**










#### Art. 045-1462-000

#### Exhausted oil drain unit 65 l

Tank capacity 65 I with level indicator Abs tool holder basin with 3 sections Recovery basin capacity 15 I with breakwater grate to drip the substituted oil filters Pneumatic air emptying (max pressure 0,5 bar)



## Art. 045-1460-000


# Exhausted oil drain unit 90 I

Tank capacity 90 I with level indicator Abs tool holder basin with 3 sections Recovery basin capacity 20 I with ergonomic and 360° swivelling abs funnel with breakwater grate to drip the substituted oil filters Pneumatic air emptying (max pressure 0,5 bar)

### Art. 045-1460-E00

#### Exhausted oil drain unit 90 l


Composed like Art.045-1460-000 but with: Recovery basin capacity 15 I



# Art. 045-1465-000

### Exhausted oil drain unit 120 I

Tank capacity 120 I with level indicator Abs tool holder basin with 3 sections Recovery basin capacity 20 I with ergonomic and 360° swivelling abs funnel with breakwater grate to drip the substituted oil filters Pneumatic air emptying (max pressure 0,5 bar)





Technical data		045-1462-000	045-1460-000	045-1460-E00	045-1465-000
Basin dimensions	mm	ø 450	760X705	ø 450	760X705
Minimum height	mm	1000	1200	1200	1200
Maximum height	mm	1700	1850	1850	1850
Empting hose length	mm	2	2	2	2

For the recovery by fall of exhausted oil of the engine, the transmission and the differential of motor-vehicles on lifts.

The basin is equipped with a grate of support to drip the substituted filters, and it can be regulated according to the height.

