

PORTABLE TYRE INFLATORS WITH AUTOMATIC CHARGE



060-1582-000

Art. 060-1582-000

Approved CEE tyre inflator 12 l

with automatic charge

Tank capacity 12 l

Equipped with:


Approved gauge Ø 80 with scale 0-10 bar

1,20 m rubber hose with double clip-on connector

Art.063-1586-000 Automatic charger



060-1582-000	11,100	0,074	1
--------------	--------	-------	---



060-1583-000

Art. 060-1583-000

Approved CEE portable tyre inflator 12 l

with automatic charge with support

Tank capacity 12 l

Equipped with:


Approved gauge Ø 80 with scale 0-10 bar

1,20 m rubber hose with double clip-on connector

Support with automatic charger



060-1583-000	13,100	0,136	1
--------------	--------	-------	---



063-1586-000

Art. 063-1586-000

Automatic charger for tyre inflators

Connection M 1/2" G

Technical data		060-1582-000	060-1583-000
Max pressure tank	bar	10	10
Max working pressure	bar	8	8
Calibrated safety	bar	10	10
Approved CE Ø 80 gauge	bar	0-10	0-10

They are suitable for service stations and garages, for checking and re-establishing the tyre pressure through the inflating and deflating valve lever. They have automatic charge in order to be ready for use. The operation of inflation and deflation of the tyres will be carried out through a unique three positions lever. To have the tyre inflator ready for use it is enough to put it on the automatic charger installed on the line of the compressed air.

NOTE: APPROVED FOR PUBLIC USE