



# SWIVELLING AUTOMATIC HOSE REELS IN PAINTED STEEL FOR GASOLINE 16 bar

Equipped with:

- Black antistatic synthetic rubber hoses steel wire helix with high strength synthetic textile plies, copper wire
- Reference regulations: EN 1761 - EN 12115 ATEX (EX ZONE)
- Self-extinguishing according to: TRbf 131/2
- Galvanized steel connections
- Galvanized steel 90° swivelling joint - Viton® seals
- Compliant with ATEX directive (see ATEX regulation at page 390)



 II 2 G Ex h IIB T4 Gb X  
 II 2 D Ex h IIIC T4 Db

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
071-1418-600	95 l/min	without hose	-	F1" G - M1" G
071-1418-510	90 l/min	10 m	3/4" - 19x27	F1" G - M1" G
071-1418-515	85 l/min	15 m	3/4" - 19x27	F1" G - M1" G
071-1418-610	95 l/min	10 m	1" - 25x35	F1" G - M1" G

S-550






Article	Capacity	L. hose	Ø hose	Inlet-Outlet
071-1518-600	95 l/min	without hose	-	F1" G - M1" G
071-1518-520	83 l/min	20 m	3/4" - 19x27	F1" G - M1" G
071-1518-615	90 l/min	15 m	1" - 25x35	F1" G - M1" G

S-555



## OVERALL DIMENSIONS SWIVELLING VERSION

Mod.	A	B	C	D	E	F	G	H				
S-550	200	150	225	270	120	572	550	680	23,00	<45,00	0,130	1
S-555	250	200	225	270	170	572	550	680	27,00	<54,00	0,150	1

