

FIXED AUTOMATIC HOSE REELS IN AISI 304 STAINLESS STEEL FOR DIESEL 10 bar

Equipped with:

- Black antistatic rubber hoses
- Galvanized steel connections
- Galvanized steel - anodized aluminum 90° swivelling joint
- Viton® seals



FX-460

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
070-2308-500	80 l/min	without hose	-	F1" G - M3/4" G
070-2308-508	80 l/min	8 m	3/4"- 19x27	F1" G - M1" G



FX-550

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
070-2408-600	95 l/min	without hose	-	F1" G - M1" G
070-2408-510	90 l/min	10 m	3/4"- 19x27	F1" G - M1" G
070-2408-515	85 l/min	15m	3/4"- 19x27	F1" G - M1" G
070-2408-610	95 l/min	10m	1" - 25x35	F1" G - M1" G




FX-555

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
070-2508-600	95 l/min	without hose	-	F1" G - M1" G
070-2508-520	83 l/min	20 m	3/4"- 19x27	F1" G - M1" G
070-2508-615	90 l/min	15 m	1" - 25x35	F1" G - M1" G



FX-560

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
070-2608-600	95 l/min	without hose	-	F1" G - M1" G
070-2608-530	80 l/min	30 m	3/4"- 19x27	F1" G - M1" G
070-2608-540	75 l/min	40 m	3/4"- 19x27	F1" G - M1" G
070-2608-620	87 l/min	20 m	1" - 25x35	F1" G - M1" G
070-2608-630	85 l/min	30 m	1" - 25x35	F1" G - M1" G



OVERALL DIMENSIONS FIXED VERSION

Mod.	A	B	C	D	E	F	G	H			
FX-460	158	120	168	192	95	490	460	490	16,50<23,00	0,094	1
FX-550	200	150	225	270	120	590	550	600	22,00<45,00	0,130	1
FX-555	250	200	225	270	170	590	550	600	26,00<53,00	0,150	1
FX-560	440	390	225	270	360	590	550	600	33,00<83,00	0,240	1