

# SWIVELLING AUTOMATIC HOSE REELS IN AISI 304 STAINLESS STEEL FOR FOOD 120 ° C 15 bar

Equipped with:

- White EPDM rubber tubes with blue cover
- Regulations: DM 21/3/73 e 18/6/79 + FOOD QUALITY F.D.A.
- AISI 316 stainless steel connections
- AISI 316 stainless steel 90° swivelling joint - PTFE Seals

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	SX-400
071-2213-400	without hose	1/2"	-	F1/2"G - M1/2"G	
071-2213-410	10 m	1/2"	15 bar	F1/2"G - M1/2"G	



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	SX-460
071-2313-400	without hose	-	-	F1/2"G - M1/2"G	
071-2313-415	15 m	1/2"	15 bar	F1/2"G - M1/2"G	




Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	SX-550
071-2413-400	without hose	1/2"	-	F1/2"G - M1/2"G	
071-2413-500	without hose	3/4"	-	F1"G - M3/4"G	
071-2413-420	20 m	1/2"	15 bar	F1/2"G - M1/2"G	
071-2413-425	25 m	1/2"	15 bar	F1/2"G - M1/2"G	
071-2413-515	15 m	3/4"	15 bar	F1"G - M3/4"G	



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet	SX-555
071-2513-400	without hose	1/2"	-	F1/2"G - M1/2"G	
071-2513-500	without hose	3/4"	-	F1"G - M3/4"G	
071-2513-600	without hose	1"	-	F1"G - M1"G	
071-2513-430	30 m	1/2"	15 bar	F1/2"G - M1/2"G	
071-2513-520	20 m	3/4"	15 bar	F1"G - M3/4"G	



## OVERALL DIMENSIONS SWIVELLING VERSION

Mod.	A	B	C	D	E	F	G	H				
SX-400	150	120	168	196	95	460	400	550	13,50	<20,50	0,084	1
SX-460	150	120	168	196	95	490	460	575	17,50	<24,00	0,094	1
SX-550	200	150	225	270	120	572	550	680	23,00	<45,00	0,130	1
SX-555	250	200	225	270	170	572	550	680	27,00	<54,00	0,150	1

