

FIXED AUTOMATIC HOSE REELS IN AISI 304 STAINLESS STEEL WITHOUT HOSE

FX-400



Article	Fluid dispensed	90° swivelling joint	Seals	Inlet-Outlet
070-2201-300	Air-Water 20 bar	brass	Viton®	F3/8"G - M3/8"G
070-2201-400	Air-Water 20 bar	brass	Viton®	F1/2"G - M1/2"G
070-2205-300	Water 150 °C 400 bar	stainless steel	Viton®	F3/8"G - M3/8"G
070-2205-400	Water 150 °C 400 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2209-400	Antifreeze-Windscreen 20 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2213-400	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1/2"G - M1/2"G

FX-460



Article	Fluid dispensed	90° swivelling joint	Seals	Inlet-Outlet
070-2301-400	Air-Water 20 bar	brass	Viton®	F1/2"G - M1/2"G
070-2305-300	Water 150 °C 400 bar	stainless steel	Viton®	F3/8"G - M3/8"G
070-2305-400	Water 150 °C 400 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2309-400	Antifreeze-Windscreen 20 ba	stainless steel	Viton®	F1/2"G - M1/2"G
070-2313-400	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1/2"G - M1/2"G

FX-550



Article	Fluid dispensed	90° swivelling joint	Seals	Inlet-Outlet
070-2401-400	Air-Water 20 bar	brass	Viton®	F1/2"G - M1/2"G
070-2405-300	Water 150 °C 400 bar	stainless steel	Viton®	F3/8"G - M3/8"G
070-2405-400	Water 150 °C 400 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2408-600	Diesel 10 bar	galvanized steel	Viton®	F1"G - M1"G
070-2409-500	AdBlue® 20 bar	stainless steel	Viton®	F3/4"G - M3/4"G
070-2413-400	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1/2"G - M1/2"G
070-2413-500	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1"G - M3/4"G
070-2418-600	Gasoline 16 bar	galvanized steel	Viton®	F1"G - M1"G

FX-555



Article	Fluid dispensed	90° swivelling joint	Seals	Inlet-Outlet
070-2502-400	Air-Water 20 bar	brass	Viton®	F1/2"G - M1/2"G
070-2502-600	Air-Water 20 bar	brass	Viton®	F1"G - M1"G
070-2505-300	Water 150 °C 400 bar	stainless steel	Viton®	F3/8"G - M3/8"G
070-2505-400	Water 150 °C 400 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2508-600	Diesel 10 bar	galvanized steel	Viton®	F1"G - M1"G
070-2513-400	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1/2"G - M1/2"G
070-2513-500	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1"G - M3/4"G
070-2513-600	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1"G - M1"G
070-2518-600	Gasoline 16 bar	stainless steel	Viton®	F1"G - M1"G

FX-560



Article	Fluid dispensed	90° swivelling joint	Seals	Inlet-Outlet
070-2602-600	Air-Water 20 bar	brass	Viton®	F1"G - M1"G
070-2605-400	Water 150 °C 400 bar	stainless steel	Viton®	F1/2"G - M1/2"G
070-2608-600	Diesel 10 bar	galvanized steel	Viton®	F1"G - M1"G
070-2613-400	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1/2"G - M1/2"G
070-2613-500	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1"G - M3/4"G
070-2613-600	Food quality F.D.A. 15 bar	stainless steel	PTFE	F1"G - M1"G
070-2618-600	Gasoline 16 bar	stainless steel	Viton®	F1"G - M1"G

OVERALL DIMENSIONS FIXED VERSION

Mod.	A	B	C	D	E	F	G	H	Kg	m ³	Nº
FX-400	158	120	168	192	95	460	400	435	12,50	0,084	1
FX-460	158	120	168	192	95	490	460	490	16,50	0,094	1
FX-550	200	150	225	270	120	590	550	600	22,00	0,130	1
FX-555	250	200	225	270	170	590	550	600	26,00	0,150	1
FX-560	440	390	225	270	360	590	550	600	33,00	0,240	1

