

SWIVELLING CLOSED HOSE REELS IN PAINTED STEEL

FOR OIL FROM 160 TO 180 bar

Equipped with:

- Black synthetic rubber hoses 1SC
- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
075-4506-400	without hose	-	-	F1/2"G - M1/2"G
075-4506-318	18 m	3/8"	180 bar	F1/2"G - M1/2"G
075-4506-410	10 m	1/2"	160 bar	F1/2"G - M1/2"G
075-4506-415	15 m	1/2"	160 bar	F1/2"G - M1/2"G

CS-500



FOR GREASE FROM 330 TO 400 bar

Equipped with:

- Black synthetic rubber hoses 2SC
- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
075-4507-200	without hose	-	-	M1/4"G - M1/4"G
075-4507-300	without hose	-	-	M3/8"G - M3/8"G
075-4507-110	10 m	1/4"	400 bar	M1/4"G - M1/4"G
075-4507-115	15 m	1/4"	400 bar	M1/4"G - M1/4"G
075-4507-118	18 m	1/4"	400 bar	M1/4"G - M1/4"G
075-4507-310	10 m	3/8"	330 bar	M3/8"G - M3/8"G
075-4507-315	15 m	3/8"	330 bar	M3/8"G - M3/8"G

CS-500




FOR ANTIFREEZE - WINDSCREEN - AdBlue® 20 bar

Equipped with:

- Black antistatic synthetic rubber EPDM hoses
- AISI 316 stainless steel connections
- AISI 316 stainless steel 90° swivelling joint
- Viton® seals
- Stainless steel reel shaft

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
075-4509-400	without hose	-	-	F1/2"G - M1/2"G
075-4509-410	10 m	1/2"	20 bar	F1/2"G - M1/2"G
075-4509-415	15 m	1/2"	20 bar	F1/2"G - M1/2"G

CS-500



CS-500

23,600<30,550

0,094

1