




FIXED MANUAL HOSE REELS IN PAINTED STEEL FOR WATER HOSES 150 °C FROM 200 TO 400 bar


Equipped with:


- AISI 316 stainless steel connections
- AISI 304 stainless steel 90° swivelling joint
- Teflon seals
- Revolving flick folding handgrip

Article	Equipped	Hose reel capacity	Inlet-Outlet	FM-400
077-1205-300	without hose	Ø 3/8" - max 15 m	F1/2"G - M3/8"G	
077-1205-400	without hose	Ø 1/2" - max 10 m	F1/2"G - M1/2"G	



Article	Equipped	Hose reel capacity	Inlet-Outlet	FM-460
077-1305-300	without hose	Ø 3/8" - max 18 m	F1/2"G - M3/8"G	
077-1305-400	without hose	Ø 1/2" - max 15 m	F1/2"G - M1/2"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FM-550
077-1405-400	without hose	Ø 1/2" - max 25 m	F1/2"G - M1/2"G	
077-1405-500	without hose	Ø 3/4" - max 15 m	F1"G - M3/4"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FM-555
077-1505-400	without hose	Ø 1/2" - max 30 m	F1/2"G - M1/2"G	
077-1505-500	without hose	Ø 3/4" - max 20 m	F1"G - M3/4"G	
077-1505-600	without hose	Ø 1" - max 15 m	F1"G - M1"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FM-560
077-1605-400	without hose	Ø 1/2" - max 50 m	F1/2"G - M1/2"G	
077-1605-500	without hose	Ø 3/4" - max 40 m	F1"G - M3/4"G	
077-1605-600	without hose	Ø 1" - max 30 m	F1"G - M1"G	

OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G			
FM-400	158	120	168	192	95	400	435	9,85<9,85	0,084	1
FM-460	158	120	168	192	95	460	500	11,31<11,34	0,094	1
FM-550	200	150	225	270	120	550	600	16,21<16,83	0,130	1
FM-555	250	200	225	270	170	550	600	17,77<17,83	0,150	1
FM-560	440	390	225	270	360	550	600	25,75<26,38	0,240	1

