

FIXED MANUAL HOSE REELS IN AISI 304 STAINLESS STEEL FOR WATER HOSES 150 °C FROM 200 TO 400 bar

Equipped with:

- AISI 316 stainless steel connections
- AISI 304 stainless steel 90° swivelling joint
- Teflon seals
- AISI 304 stainless steel revolving flick folding handgrip



FMX-400

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2205-300	without hose	Ø 3/8" - max 15 m	F1/2"G - M3/8"G
077-2205-400	without hose	Ø 1/2" - max 10 m	F1/2"G - M1/2"G



FMX-460

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2305-300	without hose	Ø 3/8" - max 18 m	F1/2"G - M3/8"G
077-2305-400	without hose	Ø 1/2" - max 15 m	F1/2"G - M1/2"G



FMX-550

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2405-400	without hose	Ø 1/2" - max 25 m	F1/2"G - M1/2"G
077-2405-500	without hose	Ø 3/4" - max 15 m	F1"G - M3/4"G



FMX-555

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2505-400	without hose	Ø 1/2" - max 30 m	F1/2"G - M1/2"G
077-2505-500	without hose	Ø 3/4" - max 20 m	F1"G - M3/4"G
077-2505-600	without hose	Ø 1" - max 15 m	F1"G - M1"G



FMX-560

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2605-400	without hose	Ø 1/2" - max 50 m	F1/2"G - M1/2"G
077-2605-500	without hose	Ø 3/4" - max 40 m	F1"G - M3/4"G
077-2605-600	without hose	Ø 1" - max 30 m	F1"G - M1"G

OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G			
FMX-400	158	120	168	192	95	400	435	8,85<8,85	0,084	1
FMX-460	158	120	168	192	95	460	500	10,71<10,80	0,094	1
FMX-550	200	150	225	270	120	550	600	15,96<16,33	0,130	1
FMX-555	250	200	225	270	170	550	600	17,22<17,83	0,150	1
FMX-560	440	390	225	270	360	550	600	25,75<26,38	0,240	1

