




FIXED MANUAL HOSE REELS IN AISI 304 STAINLESS STEEL FOR OIL AND SIMILAR HOSES FROM 88 TO 180 bar


Equipped with:


- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals
- AISI 304 stainless steel revolving flick folding handgrip

Article	Equipped	Hose reel capacity	Inlet-Outlet	FMX-400
077-2206-300	without hose	Ø 3/8" - max 15 m	F1/2"G - M3/8"G	
077-2206-400	without hose	Ø 1/2" - max 10 m	F1/2"G - M1/2"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FMX-460
077-2306-300	without hose	Ø 3/8" - max 18 m	F1/2"G - M3/8"G	
077-2306-400	without hose	Ø 1/2" - max 15 m	F1/2"G - M1/2"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FMX-550
077-2406-400	without hose	Ø 1/2" - max 25 m	F1/2"G - M1/2"G	
077-2406-500	without hose	Ø 3/4" - max 15 m	F1"G - M3/4"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FMX-555
077-2506-400	without hose	Ø 1/2" - max 30 m	F1/2"G - M1/2"G	
077-2506-500	without hose	Ø 3/4" - max 20 m	F1"G - M3/4"G	
077-2506-600	without hose	Ø 1" - max 15 m	F1"G - M1"G	

Article	Equipped	Hose reel capacity	Inlet-Outlet	FMX-560
077-2606-400	without hose	Ø 1/2" - max 50 m	F1/2"G - M1/2"G	
077-2606-500	without hose	Ø 3/4" - max 40 m	F1"G - M3/4"G	
077-2606-600	without hose	Ø 1" - max 30 m	F1"G - M1"G	

OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G			
FMX-400	158	120	168	192	95	400	435	8,85<8,85	0,084	1
FMX-460	158	120	168	192	95	460	500	10,71<10,80	0,094	1
FMX-550	200	150	225	270	120	550	600	15,96<16,33	0,130	1
FMX-555	250	200	225	270	170	550	600	17,22<17,83	0,150	1
FMX-560	440	390	225	270	360	550	600	25,75<26,38	0,240	1

