

FIXED MANUAL HOSE REELS IN AISI 304 STAINLESS STEEL FOR GREASE FROM 275 TO 400 bar

Equipped with:

- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals
- AISI 304 stainless steel revolving flick folding handgrip



FMX-400

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2207-200	without hose	Ø 1/4" - max 15 m	M1/4"G - M1/4"G
077-2207-300	without hose	Ø 3/8" - max 10 m	M3/8"G - M3/8"G
077-2207-400	without hose	Ø 1/2" - max 10 m	M1/2"G - M1/2"G



FMX-460

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2307-200	without hose	Ø 1/4" - max 18 m	M1/4"G - M1/4"G
077-2307-300	without hose	Ø 3/8" - max 15 m	M3/8"G - M3/8"G
077-2307-400	without hose	Ø 1/2" - max 15 m	M1/2"G - M1/2"G



FMX-550




Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2407-300	without hose	Ø 3/8" - max 25 m	M3/8"G - M3/8"G
077-2407-400	without hose	Ø 1/2" - max 25 m	M1/2"G - M1/2"G



FMX-555

Article	Equipped	Hose reel capacity	Inlet-Outlet
077-2507-300	without hose	Ø 3/8" - max 30 m	M3/8"G - M3/8"G
077-2507-400	without hose	Ø 1/2" - max 30 m	M1/2"G - M1/2"G

OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G			
FMX-400	158	120	168	192	95	400	435	8,85<8,85	0,084	1
FMX-460	158	120	168	192	95	460	500	10,71<10,80	0,094	1
FMX-550	200	150	225	270	120	550	600	15,96<16,33	0,130	1
FMX-555	250	200	225	270	170	550	600	17,22<17,83	0,150	1

