

AUTOMATIC HOSE REELS IN PAINTED STEEL SERIES HEAVY - DUTY FOR WATER 150 °C 200 bar

Equipped with:

- Blue no trace synthetic rubber hoses 1SC
- Galvanized steel connections
- AISI 304 stainless steel 90° swivelling joint
- Teflon seals

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-1305-300	without hose	-	-	F1/2"G - M3/8"G
073-1305-400	without hose	-	-	F1/2"G - M1/2"G
073-1304-220	20 m	5/16"	200 bar	F1/2"G - F3/8"G
073-1304-315	15 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1304-318	18 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1304-415	15 m	1/2"	200 bar	F1/2"G - F1/2"G

HD-460



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-1405-300	without hose	-	-	F1/2"G - M3/8"G
073-1405-400	without hose	-	-	F1/2"G - M1/2"G
073-1404-320	20 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1404-325	25 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1404-420	20 m	1/2"	200 bar	F1/2"G - F1/2"G
073-1404-425	25 m	1/2"	200 bar	F1/2"G - F1/2"G

HD-550



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-1505-300	without hose	-	-	F1/2"G - M3/8"G
073-1505-400	without hose	-	-	F1/2"G - M1/2"G
073-1504-330	30 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1504-430	30 m	1/2"	200 bar	F1/2"G - F1/2"G

HD-555



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-1605-300	without hose	-	-	F1/2"G - M3/8"G
073-1605-400	without hose	-	-	F1/2"G - M1/2"G
073-1604-340	40 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1604-350	50 m	3/8"	200 bar	F1/2"G - F3/8"G
073-1604-440	40 m	1/2"	200 bar	F1/2"G - F1/2"G

HD-560



OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G	H	I	Kg	m³	Nº
HD-460	196	163	209	100	529	95	460	495	534	23,26<29,60	0,072	1
HD-550	230	197	324	100	644	120	550	597	649	39,92<53,40	0,120	1
HD-555	280	247	324	100	644	170	550	597	649	51,40<66,90	0,145	1
HD-560	460	427	324	100	644	350	550	597	649	60,67<75,69	0,230	1

