

AUTOMATIC HOSE REELS IN AISI 304 STAINLESS STEEL SERIES HEAVY - DUTY FOR WATER 150 °C 200 bar

Equipped with:

- Blue no trace synthetic rubber hoses 1SC
- Galvanized steel connections
- AISI 304 stainless steel 90° swivelling joint
- Teflon seals

Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-2305-300	without hose	-	-	F1/2"G - M3/8"G
073-2305-400	without hose	-	-	F1/2"G - M1/2"G
073-2304-220	20 m	5/16"	200 bar	F1/2"G - F3/8"G
073-2304-315	15 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2304-318	18 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2304-415	15 m	1/2"	200 bar	F1/2"G - F1/2"G

HDX-460



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-2405-300	without hose	-	-	F1/2"G - M3/8"G
073-2405-400	without hose	-	-	F1/2"G - M1/2"G
073-2404-320	20 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2404-325	25 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2404-420	20 m	1/2"	200 bar	F1/2"G - F1/2"G
073-2404-425	25 m	1/2"	200 bar	F1/2"G - F1/2"G

HDX-550



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-2505-300	without hose	-	-	F3/8"G - M3/8"G
073-2505-400	without hose	-	-	F1/2"G - M1/2"G
073-2504-330	30 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2504-430	30 m	1/2"	200 bar	F1/2"G - F1/2"G

HDX-555



Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
073-2605-300	without hose	-	-	F1/2"G - M3/8"G
073-2605-400	without hose	-	-	F1/2"G - M1/2"G
073-2604-340	40 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2604-350	50 m	3/8"	200 bar	F1/2"G - F3/8"G
073-2604-440	40 m	1/2"	200 bar	F1/2"G - F1/2"G

HDX-560



OVERALL DIMENSIONS

Mod.	A	B	C	D	E	F	G	H	I	Kg	m³	Nº
HDX-460	196	163	209	100	529	95	460	495	534	22,60<28,94	0,072	1
HDX-550	230	197	324	100	644	120	550	597	649	39,05<48,15	0,120	1
HDX-555	280	247	324	100	644	170	550	597	649	50,50<61,38	0,145	1
HDX-560	460	427	324	100	644	350	550	597	649	59,50<74,52	0,230	1

