

# INDUSTRIAL HOSE REELS IN PAINTED STEEL MOTORIZED 12V ELECTRIC SERIES Mod. FE-600



**FE-601**

## For air-water and diesel 20 bar

Equipped with:

- Brass swivelling joint - Viton® seals
- **Electric 12V DC motor** 449W power

| Article             | Model         | Internal reel width | Inlet-Outlet |
|---------------------|---------------|---------------------|--------------|
| <b>076-6112-600</b> | <b>FE-601</b> | 330 mm              | F1"- F1" BSP |
| <b>076-6212-600</b> | <b>FE-602</b> | 440 mm              | F1"- F1" BSP |
| <b>076-6312-600</b> | <b>FE-603</b> | 550 mm              | F1"- F1" BSP |

## For water 150° C 200 bar

Equipped with:

- AISI 304 stainless steel 90° swivelling joint - Viton® seals
- **Electric 12V DC motor** 449W power

| Article             | Model         | Internal reel width | Inlet-Outlet |
|---------------------|---------------|---------------------|--------------|
| <b>076-6115-600</b> | <b>FE-601</b> | 330 mm              | F1"- F1" BSP |
| <b>076-6215-600</b> | <b>FE-602</b> | 440 mm              | F1"- F1" BSP |
| <b>076-6315-600</b> | <b>FE-603</b> | 550 mm              | F1"- F1" BSP |

## For oil and lubricants 250 bar

Equipped with:

- Galvanized steel swivelling joint - NBR seals
- **Electric 12V DC motor** 449W power

| Article             | Model         | Internal reel width | Inlet-Outlet |
|---------------------|---------------|---------------------|--------------|
| <b>076-6116-600</b> | <b>FE-601</b> | 330 mm              | F1"- F1" BSP |
| <b>076-6216-600</b> | <b>FE-602</b> | 440 mm              | F1"- F1" BSP |
| <b>076-6316-600</b> | <b>FE-603</b> | 550 mm              | F1"- F1" BSP |

## For grease 300 bar

Equipped with:

- Galvanized steel swivelling joint - NBR seals
- **Electric 12V DC motor** 449W power

| Article             | Model         | Internal reel width | Inlet-Outlet |
|---------------------|---------------|---------------------|--------------|
| <b>076-6117-600</b> | <b>FE-601</b> | 330 mm              | F1"- F1" BSP |
| <b>076-6217-600</b> | <b>FE-602</b> | 440 mm              | F1"- F1" BSP |
| <b>076-6317-600</b> | <b>FE-603</b> | 550 mm              | F1"- F1" BSP |

## Hose reel capacity

| Ø Hose      | Ø external Hose | Mod.FE-601  | Mod.FE-602   | Mod.FE-603   |
|-------------|-----------------|-------------|--------------|--------------|
| <b>1/2"</b> | 20 mm           | <b>50 m</b> | <b>100 m</b> | <b>200 m</b> |
| <b>3/4"</b> | 27 mm           | <b>30 m</b> | <b>60 m</b>  | <b>90 m</b>  |
| <b>1"</b>   | 34 mm           | <b>20 m</b> | <b>40 m</b>  | <b>60 m</b>  |

## Overall dimensions

| Model         | A   | B   | C   | D   | E   | F   | G   | H   | I   | J    | Weight | Packaging       |
|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|--------|-----------------|
| <b>FE-601</b> | 660 | 733 | 600 | 530 | 100 | 350 | 550 | 330 | 580 | 810  | 114 kg | 800X1200X950 mm |
| <b>FE-602</b> | 660 | 733 | 600 | 640 | 100 | 350 | 550 | 440 | 690 | 920  | 119 kg | 800X1200X950 mm |
| <b>FE-603</b> | 660 | 733 | 600 | 750 | 100 | 350 | 550 | 550 | 800 | 1030 | 124 kg | 800X1200X950 mm |



**FE-602**



**FE-603**

