

CONNECTION HOSES FOR HOSE REELS

TECHNICAL DATA

GREASE from 165 to 215 bar

- Black synthetic rubber hoses 2SC
- Galvanized steel connections

Article	L.hose	Ø Hose-dimension	Max pressure	Inlet - Outlet
907-0525-006	0,6 m	3/4" - 19X27,5 mm	215 bar	F3/4"G - F3/4"G
907-0535-008	0,8 m	3/4" - 19X27,5 mm	215 bar	F90° 3/4"G - F3/4"G
907-0525-015	1,5 m	3/4" - 19X27,5 mm	215 bar	F3/4"G - F3/4"G
907-0626-006	0,6 m	1" - 25,4X35,3 mm	165 bar	F1"G - F1"G
907-0636-008	0,8 m	1" - 25,4X35,3 mm	165 bar	F90° 1"G - F1"G
907-0626-015	1,5 m	1" - 25,4X35,3 mm	165 bar	F1"G - F1"G

DIESEL 10 bar

- Black antistatic syntetic rubber hoses
- Galvanized steel connections

Article	L.hose	Ø Hose-dimension	Max pressure	Inlet - Outlet
908-0516-020	2,0 m	3/4" - 19X27 mm	10 bar	M1"G - M1"G
908-0616-020	2,0 m	1" - 25X35 mm	10 bar	M1"G - M1"G

GASOLINE 16 bar

- Black antistatic synthetic rubber hoses steel wire helix with high strength syntetic textile plies, copper wire
- Reference regulations: EN 1761 - EN 12115 ATEX (EX ZONE)
- Self-extinguishing according to: TRbf 131/2
- Galvanized steel connections

Article	L.hose	Ø Hose-dimension	Max pressure	Inlet - Outlet
918-0526-006	0,6 m	3/4" - 19X27 mm	16 bar	F1"G - F1"G
918-0526-015	1,5 m	3/4" - 19X27 mm	16 bar	F1"G - F1"G
918-0626-006	0,6 m	1" - 25X35 mm	16 bar	F1"G - F1"G
918-0626-015	1,5 m	1" - 25X35 mm	16 bar	F1"G - F1"G

ANTIFREEZE - WINDSCREEN - AdBlue® 20 bar

- Black antistatic synthetic rubber EPDM hoses
- AISI 316 stainless steel connections

Article	L.hose	Ø Hose-dimension	Max pressure	Inlet - Outlet
909-0424-006	0,6 m	1/2" - 12,8X22 mm	20 bar	F1/2"G - F1/2"G
909-0424-010	1,0 m	1/2" - 12,8X22 mm	20 bar	F1/2"G - F1/2"G
909-0424-015	1,5 m	1/2" - 12,8X22 mm	20 bar	F1/2"G - F1/2"G
909-0424-020	2,0 m	1/2" - 12,8X22 mm	20 bar	F1/2"G - F1/2"G
909-0525-006	0,6 m	3/4" - 19X29 mm	20 bar	F3/4"G - F3/4"G
909-0525-010	1,0 m	3/4" - 19X29 mm	20 bar	F3/4"G - F3/4"G
909-0525-015	1,5 m	3/4" - 19X29 mm	20 bar	F3/4"G - F3/4"G

FOOD 120° C 15 bar

- White EPDM rubber tubes with blue cover
- Regulations: DM 21/3/73 e 18/6/79 + FOOD QUALITY F.D.A.
- AISI 316 stainless steel connections

Article	L.hose	Ø Hose-dimension	Max pressure	Inlet - Outlet
913-0424-006	0,6 m	1/2" - 12,8X22 mm	15 bar	F1/2"G - F1/2"G
913-0424-015	1,5 m	1/2" - 12,8X22 mm	15 bar	F1/2"G - F1/2"G
913-0525-006	0,6 m	3/4" - 19X29 mm	15 bar	F3/4"G - F3/4"G
913-0525-015	1,5 m	3/4" - 19X29 mm	15 bar	F3/4"G - F3/4"G